

SAFETY DATA SHEET (SDS)

Elution Solvent, Ethyl Acetate:Isopropanol

01. Product and Company Identification

Product Identifier:

Trade Name: Elution Solvent, Ethyl Acetate: Isopropanol (85:15)
Chemical Name: Ethyl Acetate: Isopropanol (85:15)
Catalog Number: 14040011, 14040012
Use of chemical: Laboratory chemical

Identification of Manufacturer:

Manufacturer/Supplier: Biochemical Diagnostics, Inc.
 180 Heartland Blvd., Edgewood, NY 11717
 Phone: (631) 595-9200 | Fax: (631) 595-9204
Emergency telephone number: (800) 255-3924

02. Hazard(s) Identification

Classification of substance or mixture:

Flammable liquids (Category 2)
Highly flammable liquid and vapor
 Skin irritation (Category 3) / Eye irritation (Category 2A)
Causes mild skin irritation. May cause respiratory irritation. Causes eye irritation.
 Specific target organ toxicity-single exposure (Category 3), CNS
May cause drowsiness or dizziness.

Label elements:

Hazard pictograms



Flammable



Irritant

Signal word: Danger

Hazard statements:

H225 Highly flammable liquid and vapor.
 H316 Causes mild skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P233 Keep container tightly closed.
 P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 P243 Take precautionary measures against static discharge.
 P264 Wash skin thoroughly after handling.
 P271 Use in a well-ventilated area or outdoors.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection
 P304+340 IF INHALED Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing.
 Rinse skin with water/ shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501 Dispose of contents/container.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 2
 Fire = 3
 Reactivity = 0

SAFETY DATA SHEET (SDS)

Elution Solvent, Ethyl Acetate:Isopropanol

HMIS-ratings (scale 0 - 4)

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

03. Composition/information on ingredients

Chemical Characterization: Mixture

CAS No. Description: 141-78-6, 67-63-0

Formula: Mixture Ethyl Acetate 85%
and Isopropanol (90-100% Isopropyl alcohol, 0-10% water) 15%
 $CH_3COOC_2H_5 : (CH_3)_2CHOH$

04. First aid measures

Description of first aid measures:

Inhalation: Remove to fresh air. Exposure can cause depression or stimulation of the CNS.
Consult a physician.

Ingestion: Rinse mouth with large amounts of water. Seek medical attention.

Skin Contact: Wash immediately with soap and water. Irritant with redness and pain.
Consult a physician.

Eye Contact: Rinse with thoroughly with plenty of water for at least 15 minutes. Vapors can be irritating, splashes can cause corneal and eye damage. Seek medical attention.

05. Firefighting measures

Extinguishing media: Water spray, dry chemical, alcohol-resistant foam, or carbon dioxide. Water may be ineffective.

Special Fire Fighting Procedures: Wear proper protective equipment w/Self contained breathing apparatus.

Unusual Fire and Explosion Hazards: Keep fire exposed containers cool. Heat will build pressure and may rupture closed storage containers. Sensitive to static discharge. Flammable Liquid and vapor. Dangerous fire hazard when exposed to heat of flame.

06. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Prevent further leakage if safe to do. Do not allow to enter sewers/surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders) and remove. Do not use combustible materials like saw dust. Ensure adequate ventilation.

Waste Disposal Method:

Dispose in accordance with state, local and federal regulations



SAFETY DATA SHEET (SDS)

Elution Solvent, Ethyl Acetate:Isopropanol

07. Handling and storage

Handling:

Precautions for safe handling: No special precautions are necessary if used correctly.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Further information about storage conditions: Keep receptacle tightly sealed.

Store in well-ventilated, cool, dry conditions in well-sealed receptacles.

08. Exposure controls/ personal protection

Exposure Controls:

Control parameters:

Components with limit values that require monitoring at the workplace:

141-78-6 Ethyl Acetate

PEL Long-term value: 1400 mg/m³, 400 ppm

REL Long-term value: 1400 mg/m³, 400 ppm

TLV Short-term value: 1440 mg/m³, 400 ppm

67-63-0 Isopropanol

PEL Long-term value: 980 mg/m³, 400 ppm

REL Long-term value: 980 mg/m³, 400 ppm

TLV Short-term value: 984 mg/m³, 400 ppm

Personal protective equipment:

General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

Eye Protection:



Tightly sealed goggles

Skin Protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact

Protection of Hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Respiratory Protection: In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Ventilation: Keep vapor levels as low as possible, use adequate general or local exhaust.

09. Physical and chemical properties

Appearance:

Form: Liquid

Color: Colorless

Odor: Fruity odor



SAFETY DATA SHEET (SDS)

Elution Solvent, Ethyl Acetate:Isopropanol

pH: no information found
Melting Point: -83.57°C (-118°F)
Boiling Point: 79°C/ 26.11°F
Flash Point: -4°C (25 °F)
Ignition temperature: 426 °C (799 °F)
Explosion limits: Lower: 3.5 Vol % Upper: 15 Vol %
Vapor Pressure @ 19°C: 76 mm Hg
Specific Gravity @ 20°C (68°F): 0.902 g/cm ³
Vapor Density: 3.0, Air=1
Percent Volatile: 100%
Evaporation Rate: 6
Flammable Limits in air % by volume: Lel: 2.0% Uel: 11.5%
Solubility in/ Miscibility with Water@20°C: 79 g/L

10. Stability and reactivity

Stability: Stable

Incompatibility: Avoid nitrates, acid anhydrides, aluminum, halogenated compounds, strong oxidizers, strong alkalis, or strong acids. Will attack some forms of plastic, rubber, and coatings.

Conditions to Avoid: Heat, sparks, open flame, open containers and poor ventilation. Extreme temperatures and sunlight.

Hazardous Polymerization: Will not occur

Hazardous Decomposition: Carbon dioxide and carbon monoxide may form when heated to decomposition.

11. Toxicological information

Acute toxicity:

LD/LC50 values that are relevant for classification:

- Oral LD50 5,620 mg/kg (rat)
- Inhalative LC50/4 h 45,000 mg/l (mouse)
- Dermal LD50 12,800 mg/kg (rabbit)

Potential health effects:

- On the skin:** No data available
- On the eye:** Irritating effect.
- Sensitization:** No sensitizing effects known.

12. Ecological information

Toxicity: No data available.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Mobility in soil: The product is water soluble and may spread in water systems.

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

SAFETY DATA SHEET (SDS)*Elution Solvent, Ethyl Acetate:Isopropanol***13. Disposal considerations****Waste treatment methods****Product:**

Dispose of in accordance with local, state and federal regulations.

Contaminated packaging:

Disposal must be made according to official regulations.

14. Transport Information**UN Number:**

1993

UN proper shipping name:

Flammable liquids, n.o.s. (Ethyl Acetate, Isopropanol)

Transport hazard class(es):

3

Packing group:

II

Environmental hazards:

None

Special precautions

None

15. Regulatory Information**SARA 302 Components:**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

16. Other Information**Revision B, June 2015**

The information contained herein is provided in good faith and is believed to be correct as of the date hereof. However, we make no representation as to the comprehensiveness or accuracy of the information. It is expected that individuals receiving the information will exercise their independent judgment in determining its appropriateness for a particular purpose. Accordingly, we will not be responsible for damages of any kind resulting from the use of or reliance upon such information.

No representations, or warranties, either express or implied of merchantability fitness for a particular purpose or of any other nature made hereunder with respect to the information set forth herein or to the product which the information refers.